

GU10 7W WH

Lamps

RAYTECK®

LED LAMP

CRI 80+ | 220–240V | SMD | SELV



An energy-efficient retrofit LED lamp for standard GU10 and MR16 fittings, delivering a direct halogen replacement with warm, high-quality light.

KEY FEATURES


GU10 lamp
The GU10 lamp delivers 80+ colour rendering for accurate, true-to-tone light, with a 36° beam for focused, directional accenting.
Dimmable via On/Off / Phase-cut.




TECHNICAL SPECIFICATIONS

Lamp Base	GU10
Power	7W
CCT	2700K / 3000K / 4000K / 6500K
CRI	80+
Beam Angle	36°
Luminous Flux	520 LM
Input Voltage	220–240VAC
Lamp Life	15,000 h
Energy Class	A ⁺
Dimming	On/Off / Phase-cut
Operating Temperature	45° C
Warranty	3 years


CCT OPTIONS



BEAM ANGLE OPTIONS



DIMMING OPTIONS




APPLICATIONS

- ⦿ Retrofit
- 🏠 Residential
- 🛒 Retail
- 👤 Hospitality

AVAILABLE VERSIONS

Code	Power	Luminous flux	Size
GU10-7W-WH-36°	7W	520 LM	Ø50 × H56 mm



Photometric reference: Photometric data measured at 4000K / CRI 80, Ta 25°C, nominal mains. Luminous flux tolerance ±10%. Lumen output and efficacy vary with correlated colour temperature (CCT) — warmer tones (2700–3000K) are typically lower and cooler tones (5000–6500K) higher — and reduce as CRI increases (90+ CRI is ~10–15% below 80 CRI). Full IES / LDT photometric files, LM-79 / LM-80 test reports and DIALux data are available on request.

Specifications are subject to change without prior notice