

MOON Wall Light

Outdoor

RAYTECK®

OUTDOOR

IP65



A precision-engineered LED outdoor delivering reliable, high-quality illumination.

KEY FEATURES

SMD LED outdoor

The SMD LED outdoor delivers 80+ colour rendering for accurate, true-to-tone light, housed in a die-cast aluminum body for effective heat management and a long service life. Rated IP65 for wet and fully outdoor locations.

TECHNICAL SPECIFICATIONS

Light Source	SMD LED
Power	7W
CCT	3000K
CRI	80+
Input Voltage	200–240V
Material	Die-cast aluminum
Finish	Black
IP Rating	IP65
Dimming	On/Off

CCT OPTIONS




3000K

DIMMING OPTIONS



AVAILABLE VERSIONS

Code	Power	Luminous flux	Size
OD-LX-MOON-7W-BK-3K	7W	80 LMW	Ø136xH80 mm



Photometric reference: Photometric data measured at 4000K / CRI 80, Ta 25°C, nominal mains. Luminous flux tolerance $\pm 10\%$. Lumen output and efficacy vary with correlated colour temperature (CCT) — warmer tones (2700–3000K) are typically lower and cooler tones (5000–6500K) higher — and reduce as CRI increases (90+ CRI is ~10–15% below 80 CRI). Full IES / LDT photometric files, LM-79 / LM-80 test reports and DIALux data are available on request.

Specifications are subject to change without prior notice