


FOREST LUXE 9.6W IP20


LED Strip
RAYTECK®

ST-RY-COB-9.6W-24V-IP20

IP20 | CRI 80+ | 24V DC | Cuttable



DIMENSIONS & WIRING



COB — continuous emitting line

A flexible, cuttable LED strip for linear and cove applications, delivering seamless, continuous illumination.



KEY FEATURES


COB LED LED strip

The COB LED LED strip built around San'an LEDs, delivering 80+ colour rendering for accurate, true-to-tone light. Rated IP20 for clean indoor spaces, dimmable via On/Off / Phase-cut / 0–10V / DALI-2.


TECHNICAL SPECIFICATIONS

Light Source	COB LED
Power / Meter	9.6W
CCT	2700K / 3000K / 4000K / 6500K
CRI	80+
Luminous Flux / Meter	400 lm/m
LEDs / Meter	320
Chip Brand	San'an
Input Voltage	24V DC
Cuttable Length	50 mm
PCB Width	8 mm
IP Rating	IP20
Dimming	On/Off / Phase-cut / 0–10V / DALI-2
Reel Length	5 m

CCT OPTIONS



DIMMING OPTIONS



APPLICATIONS

- Coves
- Under-cabinet
- Signage
- Architectural detailing

ACCESSORIES



Photometric reference: Photometric data measured at 3000K / CRI 90+, Ta 25°C, nominal mains. Luminous flux tolerance $\pm 10\%$. Lumen output and efficacy vary with correlated colour temperature (CCT) — warmer tones (2700–3000K) are typically lower and cooler tones (5000–6500K) higher — and reduce as CRI increases (90+ CRI is $\sim 10\text{--}15\%$ below 80 CRI). Full IES / LDT photometric files, LM-79 / LM-80 test reports and DIALux data are available on request.

Specifications are subject to change without prior notice